



EARTH, AIR AND WATER— ARE YOU AFFECTING THEM?

Your Solution Is Our Specialty

**The Draygon DRG 60/90/120/140 Waste Water Evaporators
60-140 Gallons/227-530 Liters/Hour**



Draygon Waste Water Evaporators From 2-140 Gallons/7.5-530 Liters/Hour

**Grease, oil, heavy metals, even carcinogens can be in your waste water
and must be disposed of without affecting our planet**

**Limit your risk of violating federal and local regulations with
Draygon waste water evaporators**

**Draygon Enterprises, Inc.
15 Blake Way • Osprey FL 34229 • 800-724-3610 • 941-485-9676 • FAX 941-485-3456
www.SteamDraygon.com • Questions@Draygon.com**



Your Solution Is Our Specialty

The Draygon DRG 60/90/120/140 Waste Water Evaporators

Applications

Perfect for waste streams from these applications and more:

- ▶ Parts Washing
- ▶ Printing Inks/Dyes
- ▶ Vehicle Washes
- ▶ Photo Processing
- ▶ Metal Fabrication
- ▶ Metal Finishing/Plating
- ▶ Floor Scrubbing Water
- ▶ Marina Bilge Water
- ▶ Air Condensation
- ▶ Ceramic Coating Wastes
- ▶ Compressor Condensate
- ▶ Degreasing Operations
- ▶ Screw Machine Shops
- ▶ Truck /Car Washes
- ▶ Coolants
- ▶ Most Aqueous Waste Streams

Specifications

Operating Type

Fully Automatic, PLC Controller, Six Probe Sensor System

Evaporation Rate

60-140 Gals/226-530 Liters/Hr
Evaporation rate based on water and air at 70 deg F/ 21 deg C for automatic operation, water at boiling point for one hour in batch operation. Solids or floating oil build-up in evaporation chamber will reduce rate.

Maximum Dimensions (L/W/H)

100x33x67" 254x84x170 cm (excluding stack)

Weight 1400-1460lbs/(636-664Kg)

Maximum Tank Capacity

315 Gallons/1190 Liters

Burner Fuels Natural Gas - LPG also available

Electrical Requirement

220V, 30 AMP, Single Phase

Fuel Consumption (Natural Gas)/Hr

Up to 1,400,000 Btu/(Approx 38 Cu Meters)
(Lower Gas Consumption for 60 Gal/225 Liter, 90 Gal/340 Liter, 120 Gal/454 Liter/ Hr Models)

PATENT PENDING

Advantages

Fast Payback/ROI

Up To 99% Waste Stream Reduction

Fast Installation

Easy Operation And Cleaning

Automatic Purge Valve Available

Radial Blade Exhaust Fan

Insulated—Exceptional Thermal Transfer

Multiple Safety Features

Wettable Surfaces

316L Stainless Steel
(Other materials available)

316L Stainless Steel Tank Standard AL6XN And Other Corrosion Resistant Materials Available

No Sewer Connection Required

No NPDES Discharge Permits Needed
(always check with local agencies before purchasing)

2-Year Limited Warranty

The DRG 60/90/120/140 Is Frequently Used With The DRG 2, DRG 5/7 And DRG 20/35 Run Dry Evaporators For A High Capacity/Run Dry Solution

Draygon Enterprises, Inc.

15 Blake Way • Osprey FL 34229 • 800-724-3610 • 941-485-9676 • FAX 941-485-3456
www.SteamDraygon.com • Questions@Draygon.com